



# Fellert Acoustical Plaster

## Product Data Sheet

### PRODUCT DESCRIPTION

Fellert is a hand-crafted seamless sound absorption system. The Fellert system consists primarily of fiberglass boards and acoustical plaster made from Perlite and Cotton.

### PROPERTIES

- Fellert Plaster is comprised of 30% recycled material
  - Fiberglass Board is comprised of 60% recycled material
  - Relatively easy to maintain
  - Powder products unaffected by frost
  - Pot Life of 12-18 hours
  - Excellent water vapor permeability
  - Thermal conductivity ASTM C-177 @ 75 F on 6.0 PCF 0.22
- 1" Fellert Fiberglass Board 4.55 R value*  
*1.5" Fellert Fiberglass Board 6.82 R value*

### SUITABLE GENERAL SUBSTRATES

- 5/8" Regular gypsum wallboard
- Metal ceiling grid (16" o.c. as constructed for 5/8" commercial drywall installations)
- Concrete
- Previously painted substrates

### INSTALLATION

The 1" fiberglass board is typically attached to gypsum wall board with a cementitious adhesive or mechanically attached to 16 o.c. ceiling grid.

The acoustical plaster is mixed with water and applied with a spray machine and troweled to an approximate thickness of 1/8".

Refer to the Fellert North American Installation Guide for application instructions and coverage rates.

Interested in how the Fellert Acoustical Plaster system can elevate your next architectural project? Contact your Fellert representative or visit us on the Web at [fellertna.com](http://fellertna.com)



4629 South 136th Street  
Omaha, NE 68137  
402.896.2005 | Toll Free 888.368.5893  
FAX 402.895.7238



### TEST DATA

#### Sound Absorption as per ASTM C423 Mount Type A

- NRC 0.75 with 1" fiberglass and Fellert Plaster to 5/8" GWB for Natural/Troweled finishes
- NRC 0.65–0.80 with 1" or 1.5" fiberglass and Fellert Plaster to 5/8" GWB for Ultra finish
- NRC 0.30 with Fellert Plaster only to 5/8" GWB for Natural/Troweled finishes
- NRC 0.40 with Fellert Plaster only to 5/8" GWB for Ultra finish

#### Sound Absorption as per ASTM C423 Mount Type E

- NRC 0.60 with 1" fiberglass and Fellert Plaster attached directly to ceiling grid for Natural/Troweled finishes
- NRC 0.85 with 1.5" fiberglass and Fellert Plaster attached directly to ceiling grid for Ultra finish

#### Light Reflectance as per ASTM E1477-98a

- 0.79 with Natural/Troweled finishes
- 0.83 with Ultra finish

#### Fire Testing as per ASTM E84-04 Class A

#### VOC as per ASTM D3960 Implied zero VOC product

#### Mold as per ASTM D3273/ASTM D3274

Meets testing specifications

#### IAQ Emissions Requirements of California Section 01350

Meets IAQ requirements of California section 01350.

### STORAGE

Store all materials in an enclosed dry environment and not in direct sunlight. Protect primer from frost.

### HEALTH & SAFETY CONSIDERATIONS

- When mixing any of the dry powder products, wear a respirator
- When handling and installing any fiberglass boards panels follow OSHA recommendations
- When using any of the Fellert products wear protective clothing and avoid contact with your skin whenever possible
- Wear eye protection at all times. If eye contact occurs, irrigate eye with clean water and seek immediate medical attention
- If any of the materials are swallowed, seek immediate medical attention

SA012512



4629 South 136th Street  
Omaha, NE 68137  
402.896.2005 | Toll Free 888.368.5893  
FAX 402.895.7238